

Обзор

информацию продукте



WS16-TW-11030000089



Spring-cage type Din-Rail TB, Rated voltage : 800 V, Rated current: 76 A, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.5 mm² - 16 mm², AWG: 24 - 6, Width: 12 mm, Height: 44.7mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

Преимущества продукта

- spring-cage connection technology, good anti-vibration performance;
- Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- Can be matched with marker strips to avoid incorrect insertion of wires.

Сертификация продукции



Технические данные

Чертеж изделия

3D модель

□

Overview

Connection method	spring-cage connection
Number of potentials	1
Number of rows	1
number of connections	3
electric potentials	1
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Application field	Railway industry, mechanical engineering, factory engineering, process industry, etc.
color	Gray

Dimension

NS 35/7,5 Height	45mm
End plate width	2.5mm
NS 35/15 Height	52.5mm
width	12mm
Height	44.7mm

Wiring data

Strip length	16~17mm
Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~16mm ²
Conductor cross section flexible AWG	24~6
Conductor cross section solid AWG	24~6

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Ambient temperature (storage / transport)	-5 °C ~ 70 °C
Ambient temperature (assembly)	-5 °C ~ 70 °C
Ambient temperature (execution)	-5 °C ~ 70 °C
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters

standard test	UL1059
Rated voltage (Use Group B)	600V
Rated current (Use Group B)	65A

IEC Electrical parameters

standard test	IEC60947-7-1
Pollution level	3
Overvoltage level	III
Insulating material group	I
Rated voltage (III / 3)	800V
Rated current (III / 3)	76A
Rated surge voltage	8KV

Safety test

Anti-finger touch	IP20
-------------------	------

Mechanical performance test

Mechanical performance test	Passed the test
Bending test rotation speed	10rpm
Bending test	135
Bend test lead cross section/weight	0.2mm ² /0.2kg
	16mm ² /2.9Kg
Tensile test results	Passed the test
Conductor cross-section tensile test/set point traction	0.2mm ² /10N
	16mm ² /100N

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Requirement, voltage drop	≤3.2mV
Voltage drop test results	Passed the test
Temperature rise test result	Passed the test

Аксессуары

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End cover	D-WS16-TW
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Бизнес-данные

Номер заказа	11030000089
Единица упаковки	20
Минимум для заказа	20
Вес продукции (без упаковки)	45.23