

## Обзор

информацию продукте

**WS2.5-TW-11030000231**

Spring-cage type Din-Rail TB, Rated voltage : 800 V, Rated current: 24 A, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 28 - 14, Width: 5 mm, Height: 32.45mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

## Преимущества продукта

- spring-cage connection technology, good anti-vibration performance;
- Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- Unique plug-in bridge, high circuit connection efficiency;
- Can be matched with marker strips to avoid incorrect insertion of wires.

## Сертификация продукции



## Технические данные

## Чертеж изделия

## 3D модель



## Overview

Connection method	spring-cage connection
Number of potentials	1
Number of rows	1
number of connections	3
electric potentials	1
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0
Application field	Railway industry, mechanical engineering, factory engineering, process industry, etc.
color	Gray

#### Dimension

NS 35/7,5 Height	35.45mm
NS 35/15 Height	42.95mm
width	5mm
Height	32.45mm

#### Wiring data

Strip length	9mm
Conductor cross section solid	0.2~2.5mm <sup>2</sup>
Conductor cross section flexible	0.2~2.5mm <sup>2</sup>
Conductor cross section flexible AWG	28~14
Conductor cross section solid AWG	28~14

#### Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Ambient temperature (storage / transport)	-5 °C ~ 70 °C
Ambient temperature (assembly)	-5 °C ~ 70 °C
Ambient temperature (execution)	-5 °C ~ 70 °C
Relative humidity (storage/transport)	25%~75%

#### UL Electrical parameters

standard test	UL1059
Rated voltage (Use Group B)	600V
Rated current (Use Group B)	15A

Rated voltage (Use Group C)	600V
Rated current (Use Group C)	15A
Rated voltage (Use Group D)	600V
Rated current (Use Group D)	5A

#### IEC Electrical parameters

standard test	IEC60947-7-1
Pollution level	3
Ovvoltage level	III
Insulating material group	I
Rated voltage (III / 3)	800V
Rated current (III / 3)	24A
Rated surge voltage	8KV

#### Safety test

Anti-finger touch	IP20
-------------------	------

#### Mechanical performance test

Mechanical performance test	Passed the test
Bending test rotation speed	10rpm
Bending test	135
Bend test lead cross section/weight	0.2mm <sup>2</sup> /0.2kg 2.5mm <sup>2</sup> /0.7kg
Tensile test results	Passed the test
Conductor cross-section tensile test/set point traction	0.2mm <sup>2</sup> /10N 2.5mm <sup>2</sup> /50N

#### Environmental protection

REACH SVHC	Lead 7439-92-1
------------	----------------

RoHS	No excessive harmful substances
Electrical performance test	
Requirement, voltage drop	≤3.2mV
Voltage drop test results	Passed the test
Temperature rise test result	Passed the test

---

Аксессуары	
Marking & Installation	
Marking strip	ZB5
Marker cards	DBE-1
Accessories	
End cover	D-WS2.5-TW
Bridge	WFA2.5
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

---

Номер заказа	11030000231
Единица упаковки	100
Минимум для заказа	100
Вес продукции (без упаковки)	7.88