


Обзор

информацию продукте


WSF4-TA-08A(H)-11030000386


Spring-cage type Din-Rail TB, Fuse type: Glass / ceramics / ..., connector method: Spring-cage/plug-in connector, Cross section: 0.2 mm²- 4 mm², AWG: 28 - 10, Rated current: 6.3 A, Rated voltage : 30 V, Width: 6 mm, Fuse type: G / 5 x 20, Mounting type: NS 35/7,5, NS 35/15, Color: black, 30 V DC LED

Преимущества продукта

- spring-cage connection technology, good anti-vibration performance;
- Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- Unique plug-in bridge, high circuit connection efficiency;
- Fuse terminal blocks, protection circuit;
- Can be matched with marker strips to avoid incorrect insertion of wires.

Сертификация продукции



Технические данные

Чертеж изделия

3D модель

Overview

Connection method	spring-cage connection
Number of potentials	1
Number of rows	1
number of connections	2
electric potentials	1
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...
LED voltage range(V)	30V AC/DC ... 60V AC/DC
LED voltage range(A)	0.4mA ... 0.86mA
Application field	Railway industry, mechanical engineering, factory engineering, process industry, etc.
color	Gray

Dimension

NS 35/7,5 Height	68mm
NS 35/15 Height	75.5mm
width	6mm
Height	66.6mm

Wiring data

Strip length	10~12mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section flexible AWG	28~10
Conductor cross section solid AWG	28~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Ambient temperature (storage / transport)	-5 °C ~ 70 °C
Ambient temperature (assembly)	-5 °C ~ 70 °C
Ambient temperature (execution)	-5 °C ~ 70 °C
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters

standard test	UL1059
Rated voltage (Use Group B)	30V
Rated current (Use Group B)	6.3A
Rated current (Use Group C)	6.3A
Rated voltage (Use Group D)	30V
Rated current (Use Group D)	5A

IEC Electrical parameters

standard test	IEC60947-7-3
Pollution level	3
Overtoltage level	III
Insulating material group	I
Rated voltage (III / 3)	30V
Rated current (III / 3)	6.3A
Rated surge voltage	0.8KV

Safety test

Anti-finger touch	IP20
-------------------	------

Mechanical performance test

Mechanical performance test	Passed the test
Bending test rotation speed	10rpm
Bending test	135
Bend test lead cross section/weight	0.2mm ² /0.2kg
	4mm ² /0.9kg
Tensile test results	Passed the test
Conductor cross-section tensile test/set point traction	0.2mm ² /10N
	4mm ² /60N

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Requirement, voltage drop	$\leq 3.2\text{mV}$
Voltage drop test results	Passed the test
Temperature rise test result	Passed the test

Аксессуары**Marking & Installation**

Marking strip	ZB6
Marker cards	DBE-1

Accessories

End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Бизнес-данные

Номер заказа	11030000386
Единица упаковки	100
Минимум для заказа	100
Вес продукции (без упаковки)	13.5