

Обзор

информацию продукте


WSF4-TA-11030000323


Spring-cage type Din-Rail TB, Fuse type: Glass / ceramics / ..., connector method: Spring-cage/plug-in connector, Cross section: 0.2 mm²- 4 mm², AWG: 28 - 10, Rated current: 6.3A, Rated voltage : 800 V, Width: 6 mm, Fuse type: G / 5 x 20, Mounting type: NS 35/7,5, NS 35/15, Color: black

Преимущества продукта

- spring-cage connection technology, good anti-vibration performance;
- Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- Unique plug-in bridge, high circuit connection efficiency;
- Fuse terminal blocks, protection circuit;
- Can be matched with marker strips to avoid incorrect insertion of wires.

Сертификация продукции



Технические данные

Чертеж изделия

3D модель

Overview

| | |
|-----------------------|------------------------|
| Connection method | spring-cage connection |
| Number of potentials | 1 |
| Number of rows | 1 |
| number of connections | 2 |
| electric potentials | 1 |
| Open-end side panels | Yes |
| Insulation Materials | PA |

| | |
|---|---|
| Flame retardant grade, in line with UL 94 | V0 |
| fuse | G/5 x 20 |
| Fuse type | Glass/ceramic/... |
| Application field | Railway industry, mechanical engineering, factory engineering, process industry, etc. |
| color | Gray |

Dimension

| | |
|------------------|--------|
| NS 35/7,5 Height | 68mm |
| NS 35/15 Height | 75.5mm |
| width | 6mm |
| Height | 66.6mm |

Wiring data

| | |
|--------------------------------------|----------------------|
| Strip length | 10~12mm |
| Conductor cross section solid | 0.2~4mm ² |
| Conductor cross section flexible | 0.2~4mm ² |
| Conductor cross section flexible AWG | 28~10 |
| Conductor cross section solid AWG | 28~10 |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
| Ambient temperature (storage / transport) | -5 °C ~ 70 °C |
| Ambient temperature (assembly) | -5 °C ~ 70 °C |
| Ambient temperature (execution) | -5 °C ~ 70 °C |
| Relative humidity (storage/transport) | 25%~75% |

UL Electrical parameters

| | |
|---------------|--------|
| standard test | UL1059 |
|---------------|--------|

| | |
|-----------------------------|------|
| Rated voltage (Use Group B) | 600V |
| Rated current (Use Group B) | 6.3A |
| Rated voltage (Use Group C) | 600V |
| Rated current (Use Group C) | 6.3A |
| Rated voltage (Use Group D) | 600V |
| Rated current (Use Group D) | 5A |

IEC Electrical parameters

| | |
|---------------------------|--------------|
| standard test | IEC60947-7-3 |
| Pollution level | 3 |
| Overtoltage level | III |
| Insulating material group | I |
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 6.3A |
| Rated surge voltage | 8KV |

Safety test

| | |
|-------------------|------|
| Anti-finger touch | IP20 |
|-------------------|------|

Mechanical performance test

| | |
|---|---------------------------|
| Mechanical performance test | Passed the test |
| Bending test rotation speed | 10rpm |
| Bending test | 135 |
| Bend test lead cross section/weight | 0.2mm ² /0.2kg |
| | 4mm ² /0.9kg |
| Tensile test results | Passed the test |
| Conductor cross-section tensile test/set point traction | 0.2mm ² /10N |
| | 4mm ² /60N |

Environmental protection

| | |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

Electrical performance test

| | |
|------------------------------|-----------------|
| Requirement, voltage drop | ≤3.2mV |
| Voltage drop test results | Passed the test |
| Temperature rise test result | Passed the test |

Аксессуары**Marking & Installation**

| | |
|---------------|-------|
| Marking strip | ZB6 |
| Marker cards | DBE-1 |

Accessories

| | |
|-----------|----------------------|
| Bridge | WFA4 |
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

Бизнес-данные

| | |
|------------------------------|-------------|
| Номер заказа | 11030000323 |
| Единица упаковки | 100 |
| Минимум для заказа | 100 |
| Вес продукции (без упаковки) | 13.496 |