



公差/General tolerances(mm)		公差/General tolerances(mm)	
0	>3	>5	>10
~	3	~	5
~	6	~	10
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±3.15	±4.00	±5.00
±7	±10		

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/20	/	/
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	630/32	/	/
额定脉冲电压(KV)/Rdte Impulse Voltage(KV)	8.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4/28~12		
间距/Pitch(mm)	7.0		
剥线长度/Stripping length(mm)	10~11		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

Appd: LI GL 2020.04.04

CHKD: Mao J 2020.04.04

DRAFT: Wang LX 2020.04.04

NAME: **DEGSON**® NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: WS4-DB-C01

TYPE: CUSTOMER DRAWING

WS4-DB-01P-1Y-00A(H)

SCALE: 2:1

REV

T0

1/1

ITEM	NAME OF PART	MATERIAL	NOTES
3	Spring	Stainless steel	
2	Current carrier	Copper	Sn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				

D

C

B

A

D

C

B

A