未注公差/General tolerances(mm)														
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300V/20	300V/20	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2
额定电压/电流/Rated Voltage(V)/Current(A)	500/20	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	24~10 / 0.2~4,6 (Sol)		
剥线长度/Stripping length(mm)	11~13		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		





Knife switch closed when shipment



Please refer to the 3D model, for these unmarked dimensions.



ITEM	NAME OF PART	MATERIAL	NOTES
6	Knife_Switch	PA66/Copper	Sn plated
5	Long_current_carrier	Copper	Sn plated
4	Short_current_carrier	Copper	Sn plated
3	Spring	Stainless steel	/
2	Button	PA66+25%GF	UL94V-0
1	Housing	PA66	UL94V-0

仅供参考图

签字：李根男

日期：2022.03.10

REV	ECN	DESCRIPTION	DRFT	DATE
00			毛军	2021.03.03

DEGSON

APPD:

CHKD:

DRFT: 毛军 2021.03.03

A4 mm (inch)

MATERIAL:

SURFACE:

MAT NO./REV: 11040000213-1 / 00

MAT STATUS: 样品

NAME

DS4-MT-01P-1Y-00A(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200007398	CUSTOMER DRAWING		2:1	1/1

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 未经予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。