



公差/General Tolerances(mm)	
0	>3
~	>10
3	~ 6
~	10
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.93	±1.05
±1.15	±1.60
±2.20	±2.50
0.1/10	
EZ	

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Screw	Steel	M4\Zn Plated
3	Current carrier	Copper	Sn Plated
4	Cage	Steel	Zn Plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:	LI GL 2020.05.23	NAME:	DC10-01P-1Y-00A(H)
CHKD:	Moo J 2020.05.23	DRAWING NO.:	DC10-C01
DRAFT:	Wong LX 2020.05.23	TYPE:	CUSTOMER DRAWING
SIZE:	A4	SCALE:	2:1
	(mm)		SHEET
	(inch)		1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/65	600/55	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特类等	III/3	/	/
级/Pollution Degree	/	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/57	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N.m/Lb.in)	M4, 1.54/14		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)	0.5~10/20~6		
侧面/Pitch(mm)	8.0		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD  
宁波高松电子有限公司