



未注公差/General tolerances(mm)												
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20

DC 10-01P-11-300A(H)			
UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/65	600/65	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/57	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M4, 1.54/14		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	20~6 / 0.5~10		
间距/Pitch(mm)/线数范围/Poles	10.0/01P		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn plated
2	Screw	Steel	M4\Zn Plated
1	Housing	PA66	Grey

		MATERIAL:	SURFACE/COLOR:	
APPD: 李根芳	2022.04.13	MAT NO./REV: /	/ 00	
CHKD: 马恩开	2022.04.11	NAME		
DRFT: 米帅	2022.04.10	DC10-01P-1Y-300A(H)		
REV	ECN	DESCRIPTION	DRAWING NO.	TYPE
00		First version	200048623	CUSTOMER DRAWING
米帅	2022.04.10	DATE	DRAWING STATUS	SCALE
			已发布	1.5:1
			SHEET	1/1

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Degson will be liable for compensation. All rights reserved for patent, utility model or design registrations. 非经书面授权, 严禁禁止转让、复制、利用、交本文件内容, 一经发现将追究法律责任。 侵权者将承担全部责任。 实用新型和外观设计专利的所有权利。