Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 非给予明确授权、否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。

未注公差/General tolerances(mm)

0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°













ITEM	NAME OF PART	MATERIAL	NOTES
8	Spring	Spring Steel	/
7	Sliding part 2	PA66	UL94V-0
6	Sliding part 1	PA66	UL94V-0
5	Groupware	/	/
4	Current carrier	copper	Sn Plated
3	Screw	steel	Zn Plated
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

	B	C	D
UL 标准/UL Standard:			
额定电压/电流/Rated Voltage(V)/Current(A)	600V/230	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	Ⅲ/3	Ⅲ/2	Ⅱ/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/232	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8		
螺丝扭矩/Torque Tightening(N· m/Lb.in)	M8, 20/177		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm^2)	2~4/0 / 25~95		
间距/Pitch(mm)/线数范围/Poles	25/N=01P		
剥线长度/Stripping length(mm)	33~35		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

REV	ECN	DESCRIPTION	DRFT	DATE
00		NEW DRAWING	赵前雄	2022.06.28

DEGSON

APPD:	李根劳	2022.06.28
CHKD:	马恩开	2022.06.28
DRFT:	赵前雄	2022.06.28

A4 (mm/inch)

MATERIAL: SURFACE:

MAT NO./REV: 11020000213-1 / 00 MAT STATUS: 小批量

NAME

DC95-01P-11-00A(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200042693	CUSTOMER DRAWING	已发布	2:1	1/1